

Modified Grover's search algorithm in $O(M + \log N)$ steps

1st February 2008

Abhishek S Gupta¹, Anirban Pathak²

Jaypee Institute of Information Technology, A-10, Sector 62, Noida-201307,
India

Abstract

The present letter proposes a modification in the well known Grover's search algorithm, which searches a database of N unsorted items in $O(\sqrt{N/M})$ steps, where M represents the number of solutions to the search problem. Concurrency control techniques and extra registers for marking and storing the solutions are used in the modified algorithm. This requires additional space but it is shown that the use of extra register and marking techniques can reduce the time complexity to $O(M + \log N)$.

1 Introduction

Searching databases is one of the most important problem in computer science and real life. This fact has motivated people to develop a large number of algorithms [1] to search different kind of databases. We are interested about a database of N unsorted items, having M solutions (where $M \ll N$). Any classical algorithm takes $O(N)$ steps to search such a database. In recent past Grover [2] has proposed a quantum algorithm for the same purpose but with a time complexity $O(\sqrt{N/M})$ [2-3]. Till now, the time complexity of the Grover's algorithm is minimum among all the algorithms that are designed for the same purpose. Tight bound on Grover searching has been studied by many people [4] but it does not establish any tight bound on quantum search in general. This fact has motivated us to explore the possibility of improvement. For this purpose we have used a technique which is well known as marking technique in classical computation.

Marking is a technique which either put a level on the target elements or on the indices associated with the target element. This technique is used widely in

¹acmabhi@rediffmail.com

²anirban.pathak@jiit.ac.in

classical computation for various purposes. Quantum analogue of the marking technique is also used by many people [5-7]. For example we can note, that Durr [6] and Chen [7] have used this technique for finding out minima and searching. In this letter we have used this technique to mark the solution states to a register of size N and we have also used two additional registers to store these marked states and the number of solutions to the search query respectively. Essentially, this registers increases the resource requirement but it considerably reduces the time complexity. The time complexity of the proposed modified Grover's algorithm is only $O(M + \log N)$. This is a considerable reduction, specially when M is small and N is large.

In section 2 we briefly discuss Grover's algorithm. The modified algorithm, its complexity and issues related to concurrency control are discussed in section 3. Finally section 4 is devoted for conclusion.

2 Grover's algorithm

As we have already stated, we are interested to search a database of N unsorted items out of which M are the solutions. In Grover's search algorithm we assign an index to each element and search on those indices. Now for our convenience if we assume that $N = 2^n$ then we can store all the indices in n qubits since the indices varies from 0 to $N - 1$. A particular instance of the search problem can conveniently be represented by a function f , which takes an integer x , in the range 0 to $N - 1$. By definition, $f(x) = 1$ if x is a solution to the search problem and $f(x) = 0$ if x is not a solution to the search problem.

Grover's algorithm uses an unitary operator as a quantum oracle which flips the oracle qubit if $f(x) = 1$. Essentially, the Oracle marks the solutions to the search problem by shifting the phase of the solution. The search oracle is applied only $O(\sqrt{N/M})$ times in order to obtain a solution on a quantum computer. This is done in following steps [3]:

1. The algorithm begins with a quantum register in the state $|0\rangle^{\otimes n}$.
2. The Hadamard transform is used to put the register in a equal superposition of $N = 2^n$ states. This is how we used to prepare the input state $|x\rangle$ for the oracle.
3. A quantum subroutine, known as the Grover iteration is repeatedly applied. The Grover iteration may be broken in following four steps:
 - a) Apply the oracle
 - b) Apply the Hadamard transformation on n qubits
 - c) Perform a conditional phase shift on the computer, with every computational basis state except $|0\rangle$ receiving a phase shift of -1
 - d) Apply the Hadamard transformation on n qubits.

3 Modified search algorithm

The modified search algorithm requires additional space to carry out marking and it starts with an initially unmarked additional register T of size N . The marking technique and the register used here are similar to that used in Durr's work [5-6] for finding out minima. Therefore, $T[j]$ represents a memory location which is used for marking where $0 \leq j \leq N - 1$. Apart from the register T we also need two other registers, one to store the number of solutions to the search problem and the other to store the solution of the search problem. Let us name these two registers as **COUNT** and **ANS** respectively. In the modified algorithm the first two steps are same. The modification appears only in Oracle which works as follows:

- a) The input to the Oracle is $|x\rangle$ (obtained in Step 2)
- b) For each x , such that $f(x) = 1$ mark $T[x]$ where $0 \leq x \leq N - 1$.

Thus, if $T[j]$ is marked then j represents a solution to the search problem. When $T[j]$ is marked, it will act as a trigger and a process to write j into **ANS** register will be spawn. Let this process be denoted by $P(j)$.

Now, we would like to note that the number of processes spawned is equal to the number of solutions to the search problem i.e. M and all these M processes (denoted by $P(j)$) will compete with each other to write j into the **ANS** register. Thus, some concurrency control mechanism must exist to allocate resource **ANS** to these M processes, such that mutual exclusion exists. This is a well known problem in classical computation and our registers are essentially classical, so we can use existing standard concurrency control techniques [8]. For example, we can use centralised cocurrency control technique [8]. In this case, each process $P(j)$, where $T[j]$ is marked, will send a request to Central Concurrency Controller (CCC) to write j into the **ANS** register and increment **COUNT** register. Although CCC will initially be flooded with M requests (since M solutions exist).

Any arbitrary process selection technique will work in our case. The reason behind this is explained later. For example, if we want our answers to be displayed in ascending order of index, then we have to allocate higher priority to a process with lower index value (i.e. j).

As soon as a process finishes its job, it will inform the CCC that it should select any other process that is waiting to use **ANS** and **COUNT** registers. CCC will then select another waiting process (if any) by using the same selection technique that it has used earlier. Decentralised Concurrency Control techniques [9] can also be used for the same purpose.

It is important to note that the prescribed mechanism is free from the common problems (like busy waiting, starvation, deadlock, process failure etc.) of concurrency control schemes. Busy waiting would be negligible in this case since the only tasks that each process $P(j)$ has is to write j into **ANS** register and give an increment in **COUNT** register. In our case, irrespective of any selection technique used in CCC, no process will starve indefinitely to use the **ANS** and **COUNT** registers, since total no of process $M \ll N$. At most, it may happen that due to a particular selection technique, a particular value of

index j will cause $P(j)$ to access the registers after $M - 1$ processes which is trivial. The ANS and COUNT registers can be considered as a single unit of shared resource since at a particular time, a particular process is either allowed to access both of them or not allowed to access any of them. Therefore, only one unit of shared resource exist and a deadlock will never happen in this situation. Process failure is a serious problem but the chance of process failure is very very low. In the worst case, one may have to run the algorithm multiple times to ensure correctness.

As far as data structure is concerned we have two options regarding the structure in which j is written on ANS: If we use a single register the register contents will probably change too rapidly for human perception. To correct this problem, we can allow a user input in the concurrency control mechanism which dictates when the register contents can change. On the other hand if we use N registers then the process $P(j)$ writes j at that register whose index is represented by COUNT. Thus, no user input is required in this case and hence, it will be faster than the single register case.

4 Conclusion

In the modified algorithm step 1 requires $O(\log N)$ time and step 3 requires $O(M)$ time, assuming that each process $P(j)$ requires $O(1)$ time to complete its task. Thus, the total time required would be $O(M + \log N)$. Thus we have a modified version of the existing Grover's algorithm having a considerably reduced time complexity. There is one more important point, Grover's iterations yield all solutions but as soon as we do a measurement the wave function collapses to a particular state, so we end up with only one solution. But in the present scheme we have all the solutions in hand. If in a particular case we decide to note only one solution then our algorithm's time complexity will reduce to $O(\log N)$. Since, there exists many applications of Grover algorithm, the improvement achieved in the present work opens up the possibility of improvement in all these applications.

References

- [1] T. H. Cormen, C. E. Leiserson, R. L. Rivest, C. Stein, *Introduction to Algorithms*, MIT Cambridge (2001).
- [2] L. K. Grover, *A fast quantum mechanical algorithm for database Search*, Proceedings, 28th Annual ACM Symposium on the Theory of Computing (STOC), 212 (1996).
- [3] M. A. Nielsen and I. L. Chuang, *Quantum Computation and Quantum Information*, Cambridge University Press (2000).
- [4] M. Boyer, G. Brassard, P. Hoyer, A. Tapp, *Tight Bounds on Quantum Searching*, Fortschr. Physics **46** 493 (1998).

- [5] C. Durr, M. Heiligman, P. Hoyer, M. Mhalla, *Quantum query complexity of some graph problems*, quant-ph/0401091.
- [6] C. Durr, P. Hoyer, *A quantum algorithm for finding the minimum* quant-ph/9607014.
- [7] G. Chen and Z. Diao, *An exact quantum search algorithm* www.math.tamu.edu/~zdiao/efs.pdf (2004).
- [8] P. A. Bernstein, V. Hadzilacos, N. Goodman, *Concurrency Control and recovery in database systems*, Addison-Wesley (1987).
- [9] W. Stallings, *Operating Systems-Internals and Design Principles*, Prentice-Hall (2004).